

Description

LANUFENE[®] LLF-182H is a linear low density polyethylene for general purpose blown film extrusion with high mechanical properties and good processability. LANUFENE[®] LLF-182H contains slip additive and antiblocking agent. The film produced from this resin characteristically exhibits good toughness, high tensile properties, outstanding puncture resistance and good optical properties.

Typical Properties

Property	ASTM Method	Unit	Value ⁽¹⁾
Resin Properties⁽²⁾			
Melt Index, 190°C, 2.16kg	D1238	g/10 min.	2.0
Density, @ 23°C	D1505	g/cm ³	0.918
Ultimate Tensile Strength	D638	MPa	18
Elongation	D638	%	650
Vicat Softening Temperature	D1505	°C	95
Low Temperature Brittleness	D746	°C	< -70
Film Properties⁽³⁾			
Tensile Strength at Break, MD/TD	D882	MPa	34/25
Elongation at Break, MD/TD	D882	%	700/750
1% Secant Modulus, MD/TD	D882	MPa	220/260
Dart Impact, F ₅₀	D1709/A	g	60
Haze	D1003	%	10
Gloss, 45°	D2457	-	60

1. Values are typical and should not to be interpreted as specification.
2. Test specimen prepared from compression molded sheet made according to ASTM D1926.
3. The film property has been measured on 38µm film thickness, 2:1 blow-up ratio.

Application

LANUFENE[®] LLF-182H is recommended for the manufacture of thin gauged general purpose blown films such as industrial liners, food packaging and agricultural mulching film.

